

KICKER®

L7152

**Dual Voice Coil
Subwoofer 38 cm**

Power Handling

1200 Watts RMS / 2400 Watts Max.

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	71 mm
Max. Linear Excursion	Xmax	+/- mm
Cone Area	Sd	1056 cm ²
Moving Mass	Mms	g
DC Resistance	Re	2 x 1,8 Ohms
Resonance Frequency	Fs	26,3 Hz
Mechanical Q-Factor	Qms	11,868
Electrical Q-Factor	Qes	0,565
Total Q-Factor	Qts	0,539
Equivalent Air Volume	VAS	149 L
VC Inductance	Le	mH
Flux Density	B/L	N/A
Efficiency 1W/1m	SPL	88,6 dB

Recommended Enclosure

Ported Box	
Vented Volume:	170 L
Port Area:	365 cm ²
Port Length:	35 cm

Recommended Enclosure

Ported Box	
Vented Volume:	85 L
Port Area:	262 cm ²
Port Length:	50 cm

Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Single Nomex Spider
- Dual Magnet 2 x 93,7 oz (5.313 g)
- Magnet Size: Ø190 x 48 mm
- TIL (Glass-Fibre) Voice Coil

Dimensions & Weight

External Diameter:	396 x
Mounting Diameter:	396 mm
Mounting Depth:	349 x
Shipping Weight:	349 mm



KICKER®

L7152

Power Handling

1200 Watts RMS / 2400 Watts Max.

**Dual Voice Coil
Subwoofer 38 cm**

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	71 mm
Max. Linear Excursion	Xmax	+/- mm
Cone Area	Sd	1056 cm ²
Moving Mass	Mms	g
DC Resistance	Re	2 x 1,8 Ohms
Resonance Frequency	Fs	26,3 Hz
Mechanical Q-Factor	Qms	11,868
Electrical Q-Factor	Qes	0,565
Total Q-Factor	Qts	0,539
Equivalent Air Volume	VAS	149 L
VC Inductance	Le	mH
Flux Density	B/L	N/A
Efficiency 1W/1m	SPL	88,6 dB

Recommended Enclosure

Ported Box	
Vented Volume:	170 L
Port Area:	365 cm ²
Port Length:	35 cm

Recommended Enclosure

Ported Box	
Vented Volume:	85 L
Port Area:	262 cm ²
Port Length:	50 cm

Mechanical Components

Former

Dimensions & Weight

239 mm
21,1 kg

